



3+ years



7-11 kids



30 m²



MATERIAL SPECIFICATION

- Construction made of the highest quality laminated, impregnated and double coated pine wood 90x90 mm, secured from the top with polypropylene plugs.
- Metal anchors made of galvanized steel, protecting the wood from direct contact with the ground to prevent rot and to extend the product's life.
- Decks of 76 cm by 76 cm made of eco-friendly WPC, featuring durable anti-slip and waterproof properties - recyclable, low-emission, and gentle on the environment while ensuring safe, long-lasting use.
- Roofs made of wood or PE or HDPE.
- Slides and Crawling Tubes made of durable HDPE.
- Moving elements made of durable PE, resistant to weather conditions.
- Net Climber/Rung Ladder made of stainless steel; Fireman's Pole and Challenge Ladder also constructed with stainless steel.
- Safe End Caps made of polypropylene, providing a smooth, impact-resistant barrier that enhances overall play safety
- Steel Ropes in polypropylene braid, connected with durable plastic or stainless steel elements.









1
number of slides



2
number of activity
elements



Wisdom Playgrounds International GmbH

Hauptstraße 215
09618 Grosshartmannsdorf
Germany

Mobile number: +49 162 831 92 11
p.koumoth@wisdomplaygroundsint.com

W-B001

Product Data

Length 318 cm

Width 327 cm

Total height 303 cm

Age group 3+ years

Number of users 7-11 kids

Safety zone 30 m²

Free fall height 200 cm

The height of the platforms 120 cm

In accordance with norm EN 1176

Availability of spare parts YES

Data is subject to change without prior notice.

Important Information

- Equipment designed for individuals with disabilities and suitable for public playgrounds;
- Equipment has a certificate from an accredited organization or a declaration of conformity;
- No sharp edges or gaps that could pose a risk of injury to the head, fingers, or other body parts;
- Should be anchored on a flat surface.
- Renders for reference purpose only, actual equipment appearance and color may differ;

5 years Warranty:

- Rope & net constructions
- Graphic print on transparent Polycarbonate panels
- Springs used for the spring riders & seesaws

15 years Warranty:

- Robinia wood items against severe rot.
- High-pressure laminate panels (HPL)
- High density polyethelene (HDPE) panels.
- Aluminum parts
- Highly dynamic steel play structures

10 years Warranty:

- Pinewood items against severe rot.
- Pre-galvanized steel posts with painted top layer
- Painted surface on galvanized or aluminum metal components
- Stainless steel slides
- Structural failure of LLDPE parts as slides, climber, ...
- Solid plastic items
- Transparent PC (polycarbonate) items
- Wood-plastic composite decks (WPC)

2 years Warranty:

- Moveable plastic & metal parts
- Sunshades structure
- Painted softwood parts with important coating degradation.
- And all other items not listed here aboved



www.wisdomplaygroundsint.com

Examples of commonly used shock-absorbing materials, their required thickness, and the maximum fall height they can safely support.

Material ^a	Description	Minimum depth ^b	Free fall heights
Where the installed surfacing is verified (e.g. sieve test) as being in accordance with this table or carries a test report according to EN 1177, no additional testing is required	mm	mm	mm
Turf/topsoil	---	---	≤1 000 ^d
Bark	20 to 80 particle size	200	≤2000
		300	≤3000
Woodchip	5 to 30 particle size	200	≤2000
		300	≤3000
Sand or gravel ^c	0,25 to 8 grain size	200	≤2000
		300	≤3000
Other materials and other depths	As tested according to EN 1177		Critical fall height as tested

- a For further information on specific material properly prepared for use in children's playgrounds see CEN/TR 16598 (Collection of Rationales for EN 1176-1 requirements).
- b For loose particulate material, add 100 mm to the minimum depth to compensate for displacement (see 4.2.8.5.1)
- c Sand and gravel shall be well rounded and washed to eliminate most of the silt or clay particles, Washed sand or gravel is considered to be from alluvial (naturally eroded) deposits and free from most silt or clay particles. For gravel this may commonly be described as 'pea shingle'. Uniformity coefficient $D_{60}/D_{10} < 3,0$. Grain size can be identified by use of a sieve test, as in EN 933-1 (see Annex G).
- d See NOTE 2 in 4.2.8.5.2.

